Safety Equipment Checklist

Share this contact informati Date of Check:	ion with others)	
Yacht Name		
Skipper Name:		
• •		
Offshore Email Address:		
SAT phone number:		
Yellow Brick ID:		
EPIRB ID:		
Yacht Call Sign:		
Yacht MMSI Number:		
☐ 30% of crew including	Training ng skipper and watch captains participating should ha	ave recently completed
a safety-at-sea cour		ave recently completed
At least one crewme	ember should have medical training with at least First	Aid and CPR
certification.	ectronic Man Overboard marker by dropping an objec	t overboard, activating the
	ing out of sight and then successfully retrieving that o	
	or at dockside, successfully recover onboard a crew	•
For Double Handed	vessels, each crew member shall demonstrate recov	very of the other crew member.
	Below Deck	
☐ A durable waterproc	of Safety Equipment Location Chart should be display	red where it can best be seen,
marked with the loca	ation of all safety equipment.	
A durable waterproc can best be seen.	of Thru-Hull Chart showing the location of all through-	hulls should be display where i
☐ A durable waterprod	of Emergency Radio Procedures Chart showing yacht	
	os, SAT Phone, Yellow Brick, etc. where it can best be ent AND charts for this voyage (not solely electronic) I	
equipment.	The AND Charts for this voyage (not solely electronic) i	Light list and chart plotting
☐ Emergency water –	1 Gallon per crew member in stout 1 gal. containers	
	at least two and no fewer than required by the yacht's	country of registry, readily
	le and different parts of the yacht. e pumps (one in cockpit near helm, second one belove	w deck) with lanvards attached
to handles & two (2)	buckets w/lanyards. Test all bilge pumps for proper	
	uipment including VHF Emergency Radio Antenna.	and the second built
fitting.	control plugs of proper sizes with lanyard attached to	each through-hull
	be adjacent to every cooking device with open flame.	
	mbination of appropriate size chain & rode ready for i	immediate use. Shackle pins
seized with wire.	chlight and flashlights with spare batteries and bulbs.	
First aid kit and mar		
Foghorn.		
Emergency steering		
I I Loois and spare par	rts including A tool canable of cutting the largest shro	ug on the hoat

	Yacht's name shall be on miscellaneous buoyant equipment. (Life jackets, cushions, lifebuoys, life
	slings, grab bags, etc.) Marine grade retro-reflective material shall be fitted to lifebuoys, life slings, life rafts, and life jackets.
片	EPIRB 406 MHZ tested & Reg. Docs. Unit shall be water & manually activated.
H	Inflatable life buoys (MOM) or similar type must be certified within one year
Ħ	Storm and heavy weather sails.
一百	Drogue or sea-anchor with appropriate rode.
	Life jackets for all crew members with retro-reflective tape fitted with thigh straps or a full safety harness whistle and waterproof light. If inflatable PFDs are used they shall be inflated and inspected annually. Service dates shall be marked on each PFD. It is recommended that all inflatable PFDs be integrated with safety harnesses. Inspect cartridges for proper installation and if over one (1) year old replace and properly insert new cartridge. Must have name of vessel or crew member and date of inspection on unit. Safety harnesses w/tethers for each crewmember if not integrated into PFD. All heavy objects such as batteries, floorboards, and galley stove shall be secured to prevent coming loose in the event of knock-down or roll-over.
	On Deck
	Alternate navigation lights.
	Radar Reflector.
닏	Main companionway shall have the retaining device to prevent loss of washboards.
님	Stainless steel uncoated wire lifelines of proper size. Cockpit locker have latches for heavy weather.
H	A marine magnetic compass, independent of any power supply, permanently installed and correctly
ш	adjusted with deviation card.
	A magnetic compass capable of being used for steering which may be hand-held.
	Jack lines properly rigged unobstructed on port and starboard side between bow and stern.
	Watertight, high-powered searchlight and watertight flashlights suitable for searching for a person
	overboard at night and for collision avoidance.
	Life Rafts must be packed in transportable rigid container or canister and stowed where it can be brought to lifelines or launched within 15 seconds. Life Rafts must have current inspection certificate.
	Each life raft shall be equipped with a grab bag with recommended contents.
H	"Life sling" style recovery system w/150' proper size polypropylene and independently,
H	Man Overboard Module (buoy with drogue, strobe, whistle flag), not attached to the vessel.
H	Yacht shall be equipped with a GPS capable of recording a man overboard position within 10 seconds
_	and monitoring that position.
	Pyrotechnic Check List
	Six (6) – SOLAS Approved Red parachute flares Cat.1 Exp. Date:
	Four (4) - SOLAS Approved Red hand flares Cat. 1 Exp. Date:
	Two (2) - SOLAS Approved Orange smoke flares Cat. 1 Exp. Date:
Recor	nmendations:
_	
	Draw boat batteries down; service, recharge and test prior to use. Test all electrical equipment.
	Test radio & SAT phone for distance. (Not with a neighboring boat or in same marina)
	Test all electronics aboard vessel.
	Service and test all safety equipment, engine, bilge pumps, galley equipment and marine toilet systems.